

Nylatron®

Polyamide [PA 6 + SOLID LUBRICANTS]

Nylatron® NSM
Nylatron® 703 XL

PLATES

Thicknesses [mm]	Tolerances on the thicknesses [mm]	Nylatron® NSM							
		Standard sizes per piece:							
		[610 x 1220 mm] [kg/pce ^[1]]		[1220 x 2000 mm] [kg/pce ^[1]]		[1220 x 2440 mm] [kg/pce ^[1]]		[1220 x 3050 mm] [kg/pce ^[1]]	
10	+0,5 +2,5	9,94	□	32,70	■	39,90	□	49,85	□
12		11,65	□	38,40	■	46,85	□	58,55	□
16		15,15	□	49,75	■	60,70	■	75,85	□
20		18,60	□	61,15	■	74,60	□	93,25	□
25		22,90	□	75,35	■	91,95	□	114,90	□
30	+0,5 +3,0	27,55	■	90,65	■	110,60	□	138,20	■
35		31,90	□	104,90	□	128,00	□	160,00	□
40		36,20	□	119,10	■	145,30	□	181,60	□
45		40,50	□	133,30	□	162,60	□	203,30	□
50		44,85	□	147,50	□	180,00	□	224,90	□
55	+0,5 +3,5	49,70	□	163,50	□	199,50	□	249,30	□
60		54,05	□	177,70	□	216,80	□	271,00	□
65		58,35	□	192,00	□	234,20	□	295,18	□
70		62,65	□	206,20	□	251,60	□	314,50	□
75		67,00	□	220,40	□	268,90	□	-	-
80	+0,5 +4,5	71,30	□	234,60	□	286,20	□	357,80	□
90		79,95	□	263,10	□	321,00	□	401,20	□
100		88,60	□	291,50	□	355,60	□	444,50	□

PLATES

Thicknesses [mm]	Tolerances on the thicknesses [mm]	Nylatron® 703 XL							
		Standard sizes per piece:							
		[610 x 1220 mm] [kg/pce ^[1]]		[1000 x 1220 mm] [kg/pce ^[1]]		[1220 x 2000 mm] [kg/pce ^[1]]		[1220 x 3050 mm] [kg/pce ^[1]]	
10	+0,5 +2,5	8,26	■	15,90	□	31,90	□	41,30	■
16		13,20	■	24,30	□	48,50	□	66,10	■
20		16,50	■	29,80	□	59,60	□	82,60	■
30		24,80	■	44,20	□	88,30	□	123,90	■
40		35,25	□	54,15	□	116,00	■	176,80	□
60	+0,5 +3,0	49,55	□	81,25	□	173,10	□	263,90	□
80		69,45	■	108,30	■	228,50	□	348,40	■

Tolerances on widths and lengths [mm]:

610 [0/+10] x 1220 [+10/+20] mm 1220 [+10/+20] x 2440 [+20/+40] mm 1220 [+10/+20] x 2000 [+10/+30] mm
1220 [+10/+20] x 3050 [+20/+40] mm

[1]: average production weights

- : **standard** item [generally available from stock; bulk quantities to be manufactured to order]
- : **semi-standard** item [generally not available from stock, minimum order quantity 1 piece]
- : **non-standard** item [generally not available from stock, manufactured to order and subject to special conditions; improved availability possible upon customer planning]