



Nylatron® MD

Polyamide [PA 6]

Nylatron® MD

ROUND RODS			
Diameters [mm]	Tolerances ^[1] on the diameters [mm]	Nylatron® MD	
		Standard length per piece: [3000 mm ^[2]]	
		[kg/pce ^[3]]	
30	+0,2 +1,2	2,75	□
50	+0,3 +2,0	7,65	□
80	+0,4 +3,0	19,48	□
Other standard length: [1000 mm ^[2]]			

^[1]: tolerances according to DIN EN 15860

^[2]: tolerance on the length -0/ +3 %

^[3]: average production weight

- : **standard** item [generally available from stock; bulk quantities to be manufactured to order]
- ▣ : **semi-standard** item [generally not available from stock, minimum order quantity 1 piece]
- : **non-standard** item [generally not available from stock, manufactured to order and subject to special conditions; improved availability possible upon customer planning]

Nylatron® MD

Polyamide [PA 6]

Nylatron® MD

PLATES			
Thicknesses [mm]	Tolerances ^[1] on the thicknesses [mm]	Nylatron® MD	
		Standard size per piece: [610x3000 mm ^[2]]	
		[kg/pce ^[3]]	
20	+0,3 +1,5	48,45	□
40	+0,5 +2,5	96,30	□
80	+0,5 +5,0	193,35	□
Other standard size: [610 x 1000 mm ^[2]]			

^[1]: tolerances according to DIN EN 15860

^[2]: tolerances: width +5/+25 mm, length -0/+3 %

^[3]: average production weight

- : **standard** item [generally available from stock; bulk quantities to be manufactured to order]
- ▣ : **semi-standard** item [generally not available from stock, minimum order quantity 1 piece]
- : **non-standard** item [generally not available from stock, manufactured to order and subject to special conditions; improved availability possible upon customer planning]