

TECHNICAL DATA SHEET **ADHESIVE TVT E-76**

Standard series PTFE/glass fabrics coated on one side with high temperature pressure sensitive silicone adhesive. Yellow textured PVC release liner is applied to the adhesive surface for ease of application.

Some application: easy release surface on heat sealing and packaging machines, ironing and pressing equipment, covering drying cylinders, lining chutes, release surface on bonding tools.

PRODUCT: Standard PTFE glass fabric self adhesive

COATING: Silicone PSA

PROPERTIES	VALUES
Standard width Please, ask for other widths	1000 mm
Backing thickness (PTFE glass)	0,075 mm
Backing weight (PTFE glass)	135 gr/m ²
Total thickness (PTFE glass and silicone PSA)	0,125 MM
Adhesion	22 N/5 cm
Temperature resistance	-73 to 260 °C

PRECAUTION REMINDERS

Please kindly pay attention our precaution reminders before applying our pressure-sensitive adhesives tapes. Prior to application, surface should be inspected carefully. Application surface should be clean, oil-free, without moisture and dirt. If the surface is extremely uneven or distorted, the tape may not adhere well. When applying, the tapes may require some pressure through roller, hand or press. Once applied, please allow sufficient time for full adhesive strength.

GENERAL STORAGE CONDITIONS

Best stored between 10°C-27°C, 25-50% relative humidity, out of direct sunlight.

The product does not contain banned substances as described in RoHS directive and will not affect RoHS compliance.

Note: nominal thickness, weight and tensile strength values are typical and are not intended as a specification minimum. Weight tolerance $g/m^2 = \pm 5\%$. All technical data are based on average values. These values are not intended for use in preparing specifications. Technical information contained herein are based on test results we believe to be reliable, but they are not to be construed in any manner as warranties expressed. All data is subject to change without notice.